



UNITED STATES PATENT APPLICATION
FOR

**METHOD FOR FABRICATION OF CERAMIC
TANTALUM NITRIDE AND IMPROVED
STRUCTURES BASED THEREON**

INVENTORS:

**HADI ABDUL-RIDHA
DAVID T. YOUNG
MAUREEN R. BRONGO**

EL479245992US

"EXPRESS MAIL" mailing label number

Date of Deposit 2/24/00

I hereby certify that this paper is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

(Signature)

Michael Farjami, Esq.
(Typed or Printed Name of Person Mailing Paper or Fee)

PREPARED BY:

**FARJAMI & FARJAMI LLP
4590 MacArthur Blvd.
Suite 500
Newport Beach, CA 92660**

(949) 574-2004

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

The present invention is generally in the field of materials used in semiconductor chips. In particular the present invention is in the field of ceramics and dielectrics used in semiconductor chips.

2. BACKGROUND ART

It is conventional in the art of fabrication of semiconductor chips to utilize ceramic materials for a variety of purposes. Ceramics can be used as insulators, capacitor dielectrics, barriers to diffusion, or barriers to etching. Semiconductor processing engineers continually search for new and improved non-metallic materials which can be used as insulators, capacitor dielectrics, barriers to diffusion, and barriers to etching. With the advent of copper as the interconnect metal of choice in semiconductor chips, there has come a need to accelerate the search for new and improved non-metallic materials that can be assimilated in fabrication processes which use copper as the interconnect metal.

Conventionally, tantalum nitride is fabricated using a nitrogen content of approximately 21% which results in a metallic tantalum nitride. Tantalum nitride has been used as a metallic barrier layer to prevent diffusion of copper in semiconductor chips. Fabrication of tantalum nitride, as a metal, has been integrated in fabrication processes which use copper as an interconnect metal. However, tantalum nitride has not, to applicants' knowledge, been fabricated in a ceramic mode. More particularly, a ceramic tantalum nitride has never been used in fabrication processes using copper as an

interconnect metal.

Prior to the present invention, there has been no method of taking advantage of the fact that the process of fabricating the metallic tantalum nitride has been integrated into copper processes and that the same integration of the fabrication process could be advantageous when utilizing tantalum nitride in a ceramic mode. In fact, to applicants' knowledge, prior to the present invention there has been no attempt to use tantalum nitride as a ceramic in semiconductor chips.

Due to ease of integration of the fabrication of tantalum nitride (whether in metallic mode or in ceramic mode) in copper processes, a number of advantages can result from use of tantalum nitride as a ceramic. The entire process of fabricating a ceramic tantalum nitride can be done in the same tool where copper interconnect is fabricated and without a need to "breaking vacuum." In other words, a layer of the ceramic tantalum nitride could be fabricated as a dielectric above a copper interconnect segment without having to take the semiconductor wafer out of the vacuum chamber for a separate fabrication of the dielectric. The fact that the fabrication of the ceramic tantalum nitride can be accomplished in the same vacuum chamber where copper interconnect is fabricated results in a significant increase in throughput and also reduces risk of contaminating the wafer. In this manner, capacitor structures can be built with higher throughput while reducing the risk of wafer contamination.

Also, the conventional etch stop layer in semiconductor chips has been silicon nitride. Etching various semiconductor chip structures, such as vias, is typically performed using a carbon fluoride based plasma. As such, employing an etch stop layer

such as silicon nitride is not ideal since silicon nitride reacts with fluoride. Use of a non-silicon based etch stop layer, such as the ceramic tantalum nitride, can provide a great advantage since ceramic tantalum nitride does not react with fluoride. As such, the ceramic tantalum nitride acts as a stronger etch stop layer than the conventional silicon
5 nitride.

Thus, there is need in the art to consider an alternative ceramic material whose fabrication can be easily assimilated in copper fabrication processes and which also has advantages such as providing a good barrier to etching.

09761489 044604
FOUO

SUMMARY OF THE INVENTION

The present invention is a method for fabrication of ceramic tantalum nitride and improved structures based thereon. According to the present invention, an ionized metal plasma ("IMP") tool is used to create a plasma containing tantalum ions where the plasma
5 is sustained by a mixture of nitrogen and argon gases. The percentage of nitrogen partial flow in the mixture of gases is adjusted so as to result in a layer of tantalum nitride with a nitrogen content of at least 30%. With a nitrogen content of at least 30%, the tantalum nitride becomes ceramic.

The ceramic tantalum nitride presents a number of advantages. For example, the
10 fabrication of ceramic tantalum nitride can be easily incorporated into fabrication of semiconductor chips using copper as the interconnect metal. Also, ceramic tantalum nitride can be used as an effective etch stop layer. The reason is that ceramic tantalum nitride does not react with fluoride which is a typical constituent of etchants utilized to etch silicon-based dielectrics such as silicon dioxide.

15 Further, ceramic tantalum nitride can be used as a dielectric in fabrication of a capacitor stack using copper electrodes. Since fabrication of ceramic tantalum nitride is easily assimilated with fabrication of copper, the capacitor stack utilizing ceramic tantalum nitride can be built in a single IMP tool along with the copper electrodes. The result is higher throughput and a reduced risk of contaminating the semiconductor wafer
20 since there is no need to "break vacuum" for a separate fabrication of the dielectric layer.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a graph illustrating the resistivity and nitrogen content of tantalum nitride as a function of the percentage of nitrogen partial flow.

Figure 2 illustrates the intensity of diffracted X ray for three separate samples of
5 tantalum nitride having different nitrogen contents.

Figure 3 shows a capacitor stack fabricated utilizing a ceramic tantalum nitride dielectric according to the present invention.

Figure 4 shows a via structure utilizing ceramic tantalum nitride as an etch stop layer according to the present invention and a different via structure utilizing silicon nitride as the etch stop layer.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is a method for fabrication of ceramic tantalum nitride and improved structures based thereon. The following description contains specific information pertaining to various equipment, materials, and layouts for implementation of the present invention. One skilled in the art will recognize that the present invention may be practiced with equipment, materials, and layouts different from those specifically discussed in the present application. Moreover, some of the specific details of the invention are not discussed in order to not obscure the invention. The specific details not described in the present application are within the knowledge of a person of ordinary skill in the art.

The drawings in the present application and their accompanying detailed description are directed to merely example embodiments of the invention. To maintain brevity, other embodiments of the invention which use the principles of the present invention are not specifically described in the present application and are not specifically illustrated by the present drawings.

The metallic mode of tantalum nitride is well known in the art and is used extensively in semiconductor chips. As an example, the metallic mode of tantalum nitride has been used as a metallic barrier layer to prevent diffusion of copper into neighboring silicon or silicon dioxide regions. To applicants' knowledge, tantalum nitride has been thus far fabricated only in the metallic mode and not in an amorphous ceramic mode as is disclosed and taught in the present application. The present invention is thus directed to fabricating tantalum nitride in an amorphous ceramic mode and using it (i.e. the non-

metallic tantalum nitride) as a dielectric in various structures in a semiconductor chip.

The present application also discloses certain advantages in using the non-metallic tantalum nitride in semiconductor chips.

The invention utilizes an ionized metal plasma ("IMP") technology to fabricate tantalum nitride in a ceramic mode. Briefly, IMP is a deposition technology in which atoms sputtered from a metallic target are ionized in plasma before reaching the semiconductor wafer. The ions are attracted toward the wafer by an electrical charge and deposit thinly, yet uniformly, across the entire surface of the wafer. The plasma density associated with IMP is moderate and, therefore, presents a minimal risk of damaging devices on the semiconductor wafer. Film coverage can be precisely tuned using pressure, RF power, and bias parameters without compromising other film properties such as stress and uniformity.

By way of overview, to fabricate a ceramic tantalum nitride film according to the present invention, atoms from a tantalum target are sputtered and turned into tantalum ions in a plasma sustained by argon and nitrogen gases. Figure 1 aids in describing how to fabricate a ceramic tantalum nitride film according to the present invention. Figure 1 also illustrates some of the characteristics of the ceramic tantalum nitride film produced according to the present invention. Y-axis 102 corresponds to resistivity of the tantalum nitride film in micro ohms-centimeter (or $\mu\Omega\text{-cm}$), x-axis 104 corresponds to percentage of nitrogen partial flow in the argon-nitrogen gas mixture in the plasma, and y-axis 106 corresponds the percentage of nitrogen content.

Figure 1 shows dashed curve 108 which represents the percentage of nitrogen

content in the tantalum nitride film produced by ionized metal plasma technology according to the present invention. Solid curve 110 represents the resistivity of the tantalum nitride film of the present invention in micro ohms-centimeter. As shown in Figure 1, both the percentage of nitrogen content in the tantalum nitride film represented by dashed curve 108 and the resistivity of the tantalum nitride film represented by solid curve 110 are functions of the percentage of nitrogen gas in the argon-nitrogen gas mixture sustaining the plasma.

Conventional tantalum nitride which is used in its metallic mode in semiconductor chips has a nitrogen content of approximately 21%. Referring to Figure 1, this percentage of nitrogen content results in a resistivity of approximately 150 micro ohms-centimeter. This low resistivity corresponds to the metallic phase of tantalum nitride. The fact that tantalum nitride containing approximately 21% nitrogen is metallic is also manifest by other characteristics of the "21%-nitrogen" tantalum nitride. For example, X ray diffraction ("XRD") graphs show the metallic nature of the "21%-nitrogen" tantalum nitride. Briefly, X ray diffraction is a common method for determining the crystallinity of a substance. X ray diffraction is a phenomenon in which the atoms of a crystal, by virtue of their uniform spacing, cause an interference pattern of the waves present in an incident beam of X ray. The atomic planes of the crystal act on the X ray in exactly the same manner as does a uniformly ruled grating on a beam of light. A detection device in an XRD tool determines the intensity of diffracted X ray which is an indication of the crystallinity of the matter under analysis. In its metallic mode, tantalum nitride is crystalline and its XRD graph has a relatively high intensity.

According to the present invention, an IMP tool is utilized to increase the percentage of nitrogen partial flow in the argon-nitrogen gas mixture to a degree such that the percentage of nitrogen content in the tantalum nitride reaches approximately 60% as opposed to the 21% present in the metallic tantalum nitride. With a nitrogen content of approximately 60%, tantalum nitride becomes ceramic and can be used to fabricate various unique semiconductor structures. As seen in Figure 1, tantalum nitride becomes highly resistive at nitrogen content of 60% which is an indication that it (i.e. tantalum nitride) is in a non-metallic (i.e. ceramic) mode. In one measurement, the resistivity of the ceramic tantalum nitride was determined to be 1.25 giga ohm-centimeter. Resistivity of 1.25 giga ohm-centimeter is a clear indication that the tantalum nitride is in a ceramic mode.

Another indication that tantalum nitride with nitrogen content of 60% is an amorphous ceramic is the low intensity of the diffracted X ray in its XRD graph. Referring to XRD graphs 202, 212, and 222 in Figure 2, y-axes 206, 216, and 226 correspond to the intensity of the diffracted X ray while x-axes 208, 218, and 228 correspond to the angle of the X ray incident on the tantalum nitride sample. Curves 204, 214, and 224 show the intensities of the diffracted X ray from tantalum nitride samples having, respectively, nitrogen contents of 21%, 33%, and 48%. Comparing curves 204, 214, and 224, it is seen that the intensity of the diffracted X ray for tantalum nitride with a nitrogen content of 21% (curve 204) is much greater than the intensity of the diffracted X ray for tantalum nitride with nitrogen content of 33% (curve 214) or 48% (curve 224).

The fact that tantalum nitride samples with nitrogen contents of 30% and 48% result in a

much lower intensity of the diffracted X ray indicates that their structures are not crystalline. Moreover, the intensity of the diffracted X ray for tantalum nitride with a nitrogen content of 60% is even less than those for tantalum nitride with nitrogen contents of 33% and 48%. Accordingly, tantalum nitride fabricated according to the present invention with a nitrogen content of greater than 30% is an amorphous ceramic substance.

As stated above, the ceramic tantalum nitride achieved by the present invention can be used advantageously in fabrication of a number of unique structures in semiconductor chips. By way of example and referring to Figure 3, the invention's ceramic tantalum nitride is used to fabricate a capacitor stack 300. Capacitor stack 300 comprises bottom interconnect metal layer one segment 302 which is made of copper. On top of bottom interconnect metal layer one segment 302 is a metallic tantalum nitride barrier layer 304. Metallic tantalum nitride barrier layer 304 is deposited on copper metal layer one segment 302 by employing an ionized metal plasma ("IMP") tool utilizing a tantalum target and adjusting the percentage of nitrogen partial flow in the argon-nitrogen gas mixture sustaining the plasma to a level so as to result in a metallic tantalum nitride film with a nitrogen content of approximately 21%. Metallic tantalum nitride barrier layer 304 is used to prevent diffusion of copper interconnect metal layer one segment 302.

Thin copper seed layer 306 is then electroplated on top of metallic nitride barrier layer 304. Copper seed layer 306 is electroplated using the same IMP tool in which metallic tantalum nitride barrier layer 304 was deposited on copper interconnect metal layer one segment 302. On top of copper seed layer 306 the invention's ceramic tantalum nitride layer 308 is deposited using the same IMP tool. The invention's ceramic tantalum

nitride layer 308 is deposited by using the same tantalum target that was used to fabricate metallic tantalum nitride layer 304. However, as explained earlier, the percentage of nitrogen partial flow in the argon-nitrogen gas mixture sustaining the plasma is increased to a degree so as to result in a nitrogen content of approximately 60% in the resulting ceramic tantalum nitride film.

Ceramic tantalum nitride layer 308 acts as a dielectric in capacitor stack 300. The dielectric constant of ceramic tantalum nitride layer 308 is approximately 10. This dielectric constant is even higher than the dielectric constant of silicon nitride which is conventionally used to fabricate high capacitance density capacitors (the dielectric constant of silicon nitride is approximately 8). As such, ceramic tantalum nitride layer 308 in fact results in a capacitor having a relatively high capacitance density.

Using the same IMP tool, metallic tantalum nitride barrier layer 310 is deposited on top of ceramic tantalum nitride layer 308. This is accomplished by utilizing the same tantalum target that was used to fabricate metallic tantalum nitride layer 304 and ceramic tantalum nitride layer 308. However, the percentage of nitrogen partial flow in the argon-nitrogen gas mixture sustaining the plasma is adjusted to a level so as to result in a metallic tantalum nitride film with a nitrogen content of approximately 21%. Metallic tantalum nitride barrier layer 310 is used to prevent diffusion of copper interconnect metal layer two segment 312 which is fabricated on top of metallic tantalum nitride layer 310.

Finally, an interconnect metal layer two segment 312 which is made of copper is fabricated on top of metallic tantalum nitride barrier layer 310. Interconnect metal layer

one segment 302 acts as a first electrode while interconnect metal layer two segment 312 acts as a second electrode for capacitor stack 300. The invention's capacitor stack 300 which utilizes a novel ceramic tantalum nitride layer 308 as a dielectric has a number of advantages over conventional capacitor structures in semiconductor chips.

5 One advantage of the invention's capacitor stack 300 is that it is fabricated in a single IMP tool without having to remove the semiconductor wafer from the IMP tool for fabrication of the dielectric tantalum nitride layer 308. In other words, the invention does not require that "vacuum be broken" and as such the invention results in a streamlined fabrication process for capacitor stack 300. The fact that the invention avoids "breaking
10 vacuum" and that the invention uses the same IMP tool for fabrication of all the different layers of capacitor stack 300 is significant since a higher throughput and a higher degree of automation is achieved. Moreover, the risk of contaminating the semiconductor wafer is reduced, resulting in a lower defect density. Another advantage of the invention's capacitor stack 300 is that, as stated above, ceramic tantalum nitride layer 308 has a
15 relatively high dielectric constant which results in a high capacitance density for capacitor stack 300.

Another example of an advantageous use of the ceramic tantalum nitride achieved by the present invention is its use as an "etch stop" layer. For example, it is conventional to use an etch stop layer when etching vias in semiconductor chips. The etch stop layer is
20 intended to prevent overetching the via hole since overetching would result in which etching away any metal or dielectric under the intended via hole.

A conventional etch stop material used for controlling the etching of via holes is

silicon nitride. Referring to Figure 4, via structure 410 shows via hole 420 which is etched in dielectric 412. Dielectric 412 is typically silicon dioxide, however, it can be another dielectric and in particular a low dielectric constant ("low-k") dielectric such as fluorinated silicon dioxide (also called "FSG"). Via structure 410 utilizes etch stop layer 414 which is made of silicon nitride. It is probable that an interconnect metal segment is situated below etch stop layer 414. However, in order to simplify the present discussion, instead of an interconnect metal segment, dielectric 412 is shown as occupying the area below etch stop layer 414.

As shown in via structure 410, it is possible to significantly overetch via hole 420 and etch away silicon nitride etch stop layer 414 and in fact etch far below the silicon nitride etch stop layer. The reason for the unintended overetching of via hole 420 is that dielectric 412 and etch stop layer 414 are both silicon-based materials, i.e. dielectric 412 is made of silicon dioxide and etch stop layer 414 is made of silicon nitride. As such, it is difficult to selectively etch silicon dioxide dielectric 412 without etching silicon nitride etch stop layer 414. In particular, it is conventional to use a carbon fluoride based plasma as the etchant for etching via hole 420 in silicon dioxide dielectric 412. Since fluoride reacts with and etches silicon, it is quite possible to unintentionally etch away some or all of silicon nitride etch stop layer 414 when etching via hole 420.

In contrast to the overetching phenomenon shown in via structure 410, via structure 450 in Figure 4 shows that via hole 460 is properly etched in dielectric 452 without etching below etch stop layer 454. In via structure 450, like via structure 410, dielectric 450 is typically silicon dioxide or a low-k dielectric such as fluorinated silicon

dioxide. However, etch stop layer 454 is made from the invention's ceramic tantalum nitride. As stated in relation to via structure 410, it is probable that an interconnect metal segment is situated below etch stop layer 454. However, in order to simplify the present discussion, instead of an interconnect metal segment, dielectric 452 is shown as
5 occupying the area below etch stop layer 454.

Unlike the silicon nitride etch stop layer in via structure 410, the invention's ceramic tantalum nitride etch stop layer 454 in via structure 450 does not react with the carbon fluoride based plasma which is the etchant used to etch silicon dioxide dielectric 452. Accordingly, the dielectric below tantalum nitride etch stop layer 454 remains intact
10 as shown in via structure 450 in Figure 4.

From the above description of the invention, it is manifest that various equipment, materials, and layouts can be used for implementing the concepts of the present invention without departing from its scope. Moreover, while the invention has been described with specific reference to certain embodiments, equipment, materials, and layouts, a person of
15 ordinary skills in the art would recognize that changes can be made in form and detail without departing from the spirit and the scope of the invention. The described embodiments are to be considered in all respects as illustrative and not restrictive. It should also be understood that the invention is not limited to the particular embodiments described herein, but is capable of many rearrangements, modifications, and substitutions
20 without departing from the scope of the invention.

Thus, a method for fabrication of ceramic tantalum nitride and improved structures based thereon has been disclosed.

CLAIMS

1. A method comprising the steps of:

utilizing an ionized metal plasma tool for creating a plasma containing tantalum ions, said plasma being sustained by a mixture of gases containing nitrogen;

5 depositing a layer of tantalum nitride on a semiconductor wafer wherein a percentage of nitrogen partial flow in said mixture of gases is adjusted so as to cause a nitrogen content in said layer of tantalum nitride to be at least 30%.

2. The method of claim 1 wherein said mixture of gases contains argon.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
21

etch stop layer in fabrication of a via structure in said semiconductor wafer.

7. A structure comprising:

a first capacitor electrode;

5 a second capacitor electrode;

a dielectric comprising ceramic tantalum nitride situated between said first and second capacitor electrodes.

8. The structure of claim 7 wherein said first capacitor electrode is made of

10 copper.

9. The structure of claim 7 wherein said second capacitor electrode is made of

15 copper.

10. The structure of claim 7 wherein said dielectric comprising ceramic

tantalum nitride is fabricated using a method comprising the steps of:

utilizing an ionized metal plasma tool for creating a plasma containing tantalum ions, said plasma being sustained by a mixture of gases containing nitrogen;

20 depositing said dielectric comprising ceramic tantalum nitride on said first capacitor electrode wherein a percentage of nitrogen partial flow in said mixture of gases is adjusted so as to cause a nitrogen content in said dielectric comprising ceramic tantalum nitride to be at least 30%.

11. The structure of claim 10 wherein said percentage of nitrogen partial flow in said mixture of gases is adjusted so as to cause said nitrogen content in said dielectric comprising ceramic tantalum nitride to be 60%.

5

12. A method for etching a dielectric in a semiconductor wafer, said method comprising the steps of:

forming a ceramic tantalum nitride layer as an etch stop layer in said dielectric;

etching said dielectric with an etchant wherein said etchant does not react with said

10 ceramic tantalum nitride layer.

13. The method of claim 12 wherein said dielectric is etched to create a via and wherein said etch stop layer is placed at a bottom of said via.

15 14. The method of claim 12 wherein said etchant is a plasma comprising carbon and fluoride.

15. The method of claim 12 wherein said dielectric comprises silicon dioxide.

20 16. The method of claim 12 wherein said step of forming said ceramic tantalum nitride layer includes the steps of:

utilizing an ionized metal plasma tool for creating a plasma containing tantalum

ions, said plasma being sustained by a mixture of gases containing nitrogen;

forming said ceramic tantalum nitride layer wherein a percentage of nitrogen partial flow in said mixture of gases is adjusted so as to cause a nitrogen content in said ceramic tantalum nitride layer to be at least 30%.

5

17. The method of claim 16 wherein said percentage of nitrogen partial flow in said mixture of gases is adjusted so as to cause said nitrogen content in said ceramic tantalum nitride layer to be 60%.

10 18. A method comprising the steps of:

forming a ceramic tantalum nitride layer as an etch stop layer in a silicon dioxide dielectric;

etching a via hole in a portion of said silicon dioxide dielectric situated above said ceramic tantalum nitride layer utilizing an etchant comprising fluoride, wherein said ceramic tantalum nitride layer prevents etching a portion of said silicon dioxide dielectric situated below said ceramic tantalum nitride layer.

19. The method of claim 18 wherein said step of forming said ceramic tantalum nitride layer includes the steps of:

20 utilizing an ionized metal plasma tool for creating a plasma containing tantalum ions, said plasma being sustained by a mixture of gases containing nitrogen;

forming said ceramic tantalum nitride layer wherein a percentage of nitrogen

partial flow in said mixture of gases is adjusted so as to cause a nitrogen content in said ceramic tantalum nitride layer to be at least 30%.

20. The method of claim 19 wherein said percentage of nitrogen partial flow in
5 said mixture of gases is adjusted so as to cause said nitrogen content in said ceramic tantalum nitride layer to be 60%.


09761439.014604


ABSTRACT

A method for fabrication of ceramic tantalum nitride and improved structures based thereon is disclosed. According to the disclosed method, an ionized metal plasma ("IMP") tool is used to create a plasma containing tantalum ions where the plasma is sustained by a mixture of nitrogen and argon gases. The percentage of nitrogen partial flow in the mixture of gases is adjusted so as to result in a layer of tantalum nitride with a nitrogen content of at least 30%. With a nitrogen content of at least 30%, the tantalum nitride becomes ceramic. The ceramic tantalum nitride presents a number of advantages.

For example, the fabrication of ceramic tantalum nitride can be easily incorporated into fabrication of semiconductor chips using copper as the interconnect metal. Also, ceramic tantalum nitride can be used as an effective etch stop layer. The reason is that ceramic tantalum nitride does not react with fluoride which is a typical constituent of etchants utilized to etch silicon-based dielectrics such as silicon dioxide. Further, ceramic tantalum nitride can be used as a dielectric in fabrication of a capacitor stack using copper electrodes. Since fabrication of ceramic tantalum nitride is easily assimilated with fabrication of copper, the capacitor stack utilizing ceramic tantalum nitride can be built in a single IMP tool along with the copper electrodes. The result is higher throughput and a reduced risk of contaminating the semiconductor wafer since there is no need to "break vacuum" for a separate fabrication of the dielectric layer.

FIG. 1






X RAY DIFFRACTION
SPECTROSCOPY

FIG. 2

FIG. 3

300






FIG. 4